

# Validated Filtration Solutions to Industry Leaders®

# GTCHB-Series Multi-Cartridge Band Clamp Liquid Filter Vessels

GTCHB-Series Multi-Cartridge Vessels are designed for industrial and commercial applications. Vessels are constructed of 304 or 316L stainless steel and accept DOE, 222/FLAT and 222/FIN end cartridges in 10, 20, 30 & 40 inch lengths.

## Features


- Easy access, self-centering heavy-duty bandclamp closure
- · Heavy-duty welded mounting/support legs
- Single o-ring design (Buna standard)
- Universal seal cups and compression plates allow vessels to accept DOE, 222/FLAT or 222/FIN cartridges
- Poly-coat finish (exterior only)
- 316L stainless steel cap/spring assemblies and V-posts
- 150 PSI pressure rating

#### Options

- Sanitary Porting
- Alternate Seal Materials
  - EPDM (required for NSF-61)
  - Teflon<sup>®</sup> Encapsulated Viton<sup>®</sup> ★
  - Viton® ★



NSF Certification applies for use only with drinking water. Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified. Product options denoted with asterisk (\*) are not included in the Certification.





# **Ordering Information**

| бтснв | # of<br>Cartridges | Length  | Inlet/Outlet<br>Size | Inlet/Outlet Style | Outlet              | Material    | Pressure Rating      | Surface Finish | NSF          |
|-------|--------------------|---------|----------------------|--------------------|---------------------|-------------|----------------------|----------------|--------------|
|       | 4                  | 1 = 10" | 2 = 2", (50)         | B = BSPT           | 2 = Opposite Outlet | 4 = 304 SS  | 15 = 150 PSI @ 250°F | PC = Polycoat  | Blank = None |
|       | 5                  | 2 = 20" | 3 = 3", (80)         | DN = DIN           |                     | 6 = 316L SS |                      |                | MC = NSF-61  |
|       | 7                  | 3 = 30" | 4 = 4", (100)        | F = RF Flange      |                     |             |                      |                |              |
|       | 12                 | 4 = 40" |                      | M = MNPT           |                     |             |                      |                |              |
|       | 22                 |         |                      |                    |                     |             |                      |                |              |

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required. For additional technical support, a product Performance Guide is available upon request.

SV\_GCTHB\_0524



**Corporate Office** 1201 Continental PI NE Cedar Rapids, IA 52402 USA 
 Phone

 Office:
 +1-877-603-1003

 Fax:
 +1-319-743-0220

## Online

Website: www.globalfilter.com Email: gfcustomerservice@filtrationgroup.com