

# Microfiber Liquid Filter Bags


## High Efficiency Microfiber Filter Bags

- Micron ratings from 1.0 to 50.0
- All industry-standard and custom sizes available
- Choice of steel or molded plastic snap seal V-rings
- Broad chemical compatibility
- Excellent oil-absorbing capabilities (POMF)
- Handles standard on all bags
- Efficiency ratings to 95.0%

#### **High Efficiency Bag Materials**

Microfiber materials provide high efficiencies at low micron ratings. Multi-layer technology results in true graded-density filtration, delivering significantly increased loading capacities and lower overall filtration costs.

- Polypropylene & polyester microfiber materials meet FDA regulations for food contact under CFR21, Section 177.1520
- Silicone-free construction
- High dirt holding capacity



High Efficiency Filter Bag Construction

### **High Efficiency Bag Styles**

- Standard ring bags have a galvanized steel ring (stainless steel optional) sewn in the top of the bag
- V-ring bags have a molded plastic ring sewn to the filter bag



Felt Materials	Rating (μ)								
	1A	2A	5A	10A	25A	50A			
Polyester	•	•	•	•	•	•			
Polypropylene	•	•	•	•	•	•			

#### **Ordering Information**

G	Media	Rating (µ)	Cover/Jacket	Bag Dimensions		ions	Ring Style
	PEMF = Polyester	1A	P = Standard	Size	Diam.	Length	C = Commercial Type Snap Steel Band
	POMF = Polypropylene	2A		1	7.06"	16.5"	PP = Polypropylene (rolled)
		5A		2	7.06"	32.0"	S = Standard Steel Ring
		10A		3	4.12"	8.0"	SS = Stainless Steel Ring
		25A		4	4.12"	14.0"	V = High-temp Plastic Snap Seal
		50A		7	5.5"	15.0"	
				8	5.5"	20.0"	
				9	5.5"	31.0"	
				C1	7.31"	16.5"	
				C2	7.31"	32.5"	

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required.

GLOBAL FILTER

**Corporate Office** 1201 Continental PI NE Cedar Rapids, IA 52402 USA 
 Phone

 Office:
 +1-877-603-1003

 Fax:
 +1-319-743-0220

#### Online

Website: www.globalfilter.com Email: gfcustomerservice@filtrationgroup.com

SV GPEMF-GPOMF 0624

### Validated Filtration Solutions to Industry Leaders®